Modal Vibration Test System TV 51120-MOSP


S 51120-MOSP (Example drawing) Dimensions in mm

TECHNICAL PARAMETERS Modal exciter S 51120-MOSP

Rated peak force $Sine_{pk}$/$Random_{RMS}$ [1]	200/140 N
Frequency range	DC - 5000 Hz
Main resonance frequency (free-swinging)	>6000 Hz
Max. displacement Peak-Peak	25.4 mm
Max. velocity	1.5 m/s
Suspension stiffness	4 N/mm
Effective moving mass	0.23 kg
Total mass	21 kg
Coupling thread	M6

1) Random force according to ISO 5344:2004






SCOPE OF DELIVERY, OPTIONS AND FEATURES OF THE SYSTEM

Scope of delivery:
Modal exciter
Trunnion mount
Power amplifier
Cooling blower
Connection cable (5 m)
Power cable amplifier (1.5 m)
Blower hose ø40 mm (3 m)

Options:
Rack for mounting the amplifier
Silencer
for cooling blower (Noise reduction up to 5 dB(A))
Acoustic enclosure
for cooling blower (Noise reduction 15 - 23 dB(A))
Stinger (see Modal brochure for details)
Cable extension
Factory acceptance test

Features:
Vibration isolation
Coarse filter unit
High cross-axial stiffness
Throughhole in the center of the armature for attaching tension-wire stingers
Light weight construction by using rare earth magnet
Minimum maintenance effort
Made in Germany
Servicehotline



TIRA GmbH Eisfelder Str. 23/25, 96528 Schalkau, Germany • Phone: +49 36766 280-0 • Fax: +49 36766 280-99 • Internet: www.tira-gmbh.de • Email: st@tira-gmbh.de

© TIRA GmbH • Version 05 - 2025-01-28

Subject to modifications

Modal Vibration Test System TV 51120-MOSP

TECHNICAL PARAMETERS Amplifier BAA 500

Output power$_{RMS}$	500 VA
Frequency range (small signal/full power)	DC - 180 kHz / 20 Hz - 25 kHz
Voltage-/Current mode	yes/yes
Voltage$_{RMS}$, max	45 V
Current$_{RMS}$, max. (0.1 - 20 Hz)	11.2 A (9 A)
Signal input voltage$_{PK}$	3.5 V
Distortion THD (Frequency range 40 Hz to 5 kHz)	< 0.05 %
Signal to noise ratio	> 110 dB(A)
Total mass	18 kg
Dimensions (WxHxD)	440 x 90 x 290 mm
Power supply (Standard)	1~ / N / PE 230 V±5% 50/60 Hz, CEE 7/7
Recommended fuse protection (Standard)	16 A slow
Max. power consumption at 230 V	0.35 kVA
Interlocks:	Overload, temperature, clipping


Features:
- High Signal to noise ratio of >110 dB
- Monitoring outputs for voltage and current

TECHNICAL PARAMETERS Cooling blower TB 0080

Volume flow rate	max. 80 m³/h
Total pressure difference	max. 120 hPa
Power	0.37 kW
Frequency	50 Hz
Hose diameter	40 mm
Hose length (Std.)	3 m
Total mass	10 kg
Dimensions (WxHxD)	246 x 256 x 247 mm
Sound pressure level, max.	max. 53 dB(A)
Power supply (standard)	1~ / N / PE 230 V±5% 50/60 Hz, CEE 7/7
Max. current consumption at 230 V	2.7 A

Options:
Silencer TB 0080-SI (Noise reduction up to 5 dB(A))
Dimensions (LxD): 310 x 65 mm
Mass: 0.2 kg
Acoustic enclosure TB 0080-AE (Noise reduction 15 - 23 dB(A))
Dimensions (WxHxD): 650 x 760 x 860 mm
Mass: 45 kg
Hose length according to customers request (up to 10 m)






Cooling blower TB 0080


Silencer TB 0080-SI (optional)


Acoustic enclosure TB 0080-AE (optional)

TIRA GmbH Eisfelder Str. 23/25, 96528 Schalkau, Germany • Phone: +49 36766 280-0 • Fax: +49 36766 280-99 • Internet: www.tira-gmbh.de • Email: st@tira-gmbh.de

© TIRA GmbH • Version 05 - 2025-01-28 Subject to modifications