Vibration Test System TV 51140


TECHNICAL PARAMETERS Vibration exciter S 51140

Rated peak force Sine$_{pk}$/Random$_{RMS}$ [1]	400/311 N
Frequency range	2 - 6500 Hz
Main resonance frequency	>5500 Hz
Max. displacement Peak-Peak [2]	20 mm
Max. velocity	1.5 m/s
Max. acceleration Sine/Random	100/50 g
Suspension stiffness	5 N/mm
Effective moving mass	0.4 kg
Total mass	18 kg
Armature diameter	60 mm

1) Random force according to ISO 5344:2004
2) Payload has an impact on the possible maximum displacement
For long-term tests, the load must be reduced to 80 %. Continuous operation at maximum load can cause damage.



S 51140 (Example drawing) Dimensions in mm



SCOPE OF DELIVERY, OPTIONS AND FEATURES OF THE SYSTEM

Scope of delivery:
Vibration exciter
Trunnion mount
Power amplifier
Cooling blower
Connection cable (5 m)
Power cable amplifier (1.5 m)
Blower hose ø40 mm (3 m)

Options:
Different thread inserts of armature
at customers request
Rack for mounting the amplifier
Degauss kit to reduce stray magnetic field
Silencer
for cooling blower (Noise reduction up to 8 dB(A))
Acoustic enclosure
for cooling blower (Noise reduction 15 - 23 dB(A))
Modal adapter M6
Stinger (see Modal brochure for details)
Cable extension
Factory acceptance test

Features:
Vibration isolation
Coarse filter unit
High cross-axial stiffness
Light weight construction by using
rare earth magnet
Minimum maintenance effort
Made in Germany
Servicehotline

TIRA GmbH Eisfelder Str. 23/25, 96528 Schalkau, Germany • Phone: +49 36766 280-0 • Fax: +49 36766 280-99 • Internet: www.tira-gmbh.de • Email: st@tira-gmbh.de

© TIRA GmbH • Version 10 - 2026-03-05 Subject to modifications

Vibration Test System TV 51140

TECHNICAL PARAMETERS Amplifier BDA 1300


Output power$_{RMS}$, max.	1300 VA
Frequency range	DC - 25 kHz
Voltage-/Current mode	yes/yes
Voltage$_{RMS}$, max.	72 V
Current$_{RMS}$, max.	18 A
Signal input voltage$_{PK}$	3.5 V
Distortion	< 0.1 %
Signal to noise ratio	> 100 dB
Total mass	22 kg
Dimensions (WxHxD)	440 x 90 x 450 mm
Power supply (Standard)	1~ / N / PE 230 V±5% 50 Hz, CEE 7/7
Recommended fuse protection (Standard)	16 A slow
Max. power consumption at 230 V	1.22 kVA
Interlocks:	Overload, temperature, clipping

Features:
High Signal to noise ratio of > 100 dB
Monitoring output of voltage and current

TECHNICAL PARAMETERS Cooling blower TB 0140

Volume flow rate	max. 140 m³/h
Total pressure difference	max. 150 mbar
Power	1.1 kW
Frequency	50 Hz
Hose diameter	40 mm
Hose length (Std.)	3 m
Total mass	16 kg
Dimensions (WxHxD)	286 x 302 x 292 mm
Sound pressure level, max.	max. 63 dB(A)
Power supply (Standard)	1~ / N / PE 230 V±5% 50 Hz, CEE 7/7
Max. current consumption at 400 V	7.3 A

Options:
Silencer (Noise reduction up to 8 dB(A))
  Dimensions (LxD): 308 x 82 mm
  Mass: 0.2 kg
Acoustic enclosure (Noise reduction 15 - 23 dB(A))
  Dimensions (WxHxD): 860 x 760 x 650 mm
  Mass: 45 kg
Hose length according to customers request (up to 10 m)




Cooling blower TB 0140


Silencer TB 0140-SI
(optional)


Acoustic enclosure TB 0140-AE
(optional)

TIRA GmbH Eisfelder Str. 23/25, 96528 Schalkau, Germany • Phone: +49 36766 280-0 • Fax: +49 36766 280-99 • Internet: www.tira-gmbh.de • Email: st@tira-gmbh.de

© TIRA GmbH • Version 10 - 2026-03-05 Subject to modifications